



## Poultry and Livestock Fabrics

### FABTEX 75

#### Product Data Sheet

PROPERTY	TEST METHOD	Typical
<b>Weight</b>	ASTM D5261	7.6 oz
<b>Material</b>		HDPE
<b>Color</b>	Visual	Clear
<b>Construction</b>	ASTM D3775	14 x 14
<b>Thickness</b>	ASTM D1777	15.5 Mils
<b>Grab Tensile</b>	ASTM D4632	300 x 283 lbs
<b>Grab Elongation</b>	ASTM D4632	41% x 39%
<b>Trapezoid Tear Strength</b>	ASTM D4533	50 x 44 lbs
<b>Mullen Burst</b>	ASTM D3786	440 psi
<b>Shade Factor</b>	ASTM D6567	34%

This curtain is primarily used on hog and dairy barns due to its excellent strength, UV properties, abrasion resistance and over all weatherability. This curtain is used with the seven layered curtain on the southern side of the barn.

Seller makes no warranty, express or implied, concerning the product furnished hereunder other than at the time of delivery it shall be of the quality and specifications stated herein. ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS EXPRESSLY EXCLUDED AND, TO THE EXTENT THAT IT IS CONTRARY TO THE FOREGOING SENTENCE ANY IMPLIED WARRANTY OF MERCHANTABILITY IS EXPRESSLY EXCLUDED. Any recommendations made by the Seller concerning uses or applications of said product are believed reliable and Seller makes no warranty of results to be obtained. This data sheet supersedes all previous data sheets for this style and is subject to change without notice. The effective date for this product data is 5/28/19.

**Fabtex Solutions**  
**Technical Department**  
 2556 Piney Road • Morganton, NC • 28655  
 Telephone • 828 584 1240 Fax • 828 584 0880