



Poultry and Livestock Fabrics

FABTEX 130

Product Data Sheet

PROPERTY	TEST METHOD	Typical
Weight	ASTM D5261	13 oz
Material		PVC
Color	Visual	White
Construction	ASTM D3775	1000 x 1000 denier
Thickness	ASTM D1777	16.0 Mils
Grab Tensile	ASTM D4632	190 x 185 lbs
Trapezoid Tear Strength	ASTM D4533	65 x 65 lbs
Hydrostatic Resistance		310 psi
Cold Crack		-30

This poly-vinyl coated curtain offers great flexibility and abrasion resistance.

Seller makes no warranty, express or implied, concerning the product furnished hereunder other than at the time of delivery it shall be of the quality and specifications stated herein. ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS EXPRESSLY EXCLUDED AND, TO THE EXTENT THAT IT IS CONTRARY TO THE FOREGOING SENTENCE ANY IMPLIED WARRANTY OF MERCHANTABILITY IS EXPRESSLY EXCLUDED. Any recommendations made by the Seller concerning uses or applications of said product are believed reliable and Seller makes no warranty of results to be obtained. This data sheet supersedes all previous data sheets for this style and is subject to change without notice. The effective date for this product data is 12/15/15.

Fabtex Solutions
Technical Department
2556 Piney Road • Morganton, NC • 28655
Telephone • 828 584 1240 Fax • 828 584 0880