



Poultry and Livestock Fabrics

FABTEX 55

Product Data Sheet

PROPERTY	TEST METHOD	Typical
Weight	ASTM D5261	5.3 oz
Material		HDPE
Color	Visual	Milky
Construction	ASTM D3775	12 x 12
Thickness	ASTM D1777	10.7 Mils
Grab Tensile	ASTM D4632	205 x 215 lbs
Grab Elongation	ASTM D4632	24% x 24%
Trapezoid Tear Strength	ASTM D4533	71 x 76 lbs
Mullen Burst	ASTM D3786	370 psi
Shade Factor	ASTM D6567	36.7%

This is a strong medium weight curtain with its 12 x 12 construction. This curtain is ideal for poultry houses and general curtain applications.

Seller makes no warranty, express or implied, concerning the product furnished hereunder other than at the time of delivery it shall be of the quality and specifications stated herein. ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS EXPRESSLY EXCLUDED AND, TO THE EXTENT THAT IT IS CONTRARY TO THE FOREGOING SENTENCE ANY IMPLIED WARRANTY OF MERCHANTABILITY IS EXPRESSLY EXCLUDED. Any recommendations made by the Seller concerning uses or applications of said product are believed reliable and Seller makes no warranty of results to be obtained. This data sheet supersedes all previous data sheets for this style and is subject to change without notice. The effective date for this product data is 5/13/20.

Fabtex Solutions
Technical Department
 2556 Piney Road • Morganton, NC • 28655
 Telephone • 828 584 1240 Fax • 828 584 0880