



Product Data Sheet

Pool Cover Fabric TYPICAL FABRIC PROPERTIES

Our pool cover fabric is a woven fabric comprised of high tenacity monofilament yarns

Technical Properties (Fabric)	Test Method	Value	Units
Weight	ASTM D-3776	7.0	Oz/yd ²
Tensile - Warp	ASTM D-5034	300	Lbs/in
Tensile - Fill	ASTM D-5034	330	Lbs/in
Burst	ASTM D-3786	670	PSI
Air Flow	ASTM D-737	40	CFM
Shade	ASTM D-6567	98	%
Thickness	ASTM D-5199	18	mils

The above values are typical and should not be used as minimum or maximum values. Seller makes no warranty, express or implied, concerning the product furnished hereunder other than at the time of delivery it shall be of the quality and specifications stated herein. ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS EXPRESSLY EXCLUDED AND, TO THE EXTENT THAT IT IS CONTRARY TO THE FOREGOING SENTENCE ANY IMPLIED WARRANTY OF MERCHANTABILITY IS EXPRESSLY EXCLUDED. Any recommendations made by the Seller concerning uses or applications of said product are believed reliable and Seller makes no warranty of results to be obtained. This data sheet supersedes all previous data sheets for this style and is subject to change without notice. The effective date for this product data is 7/1/14.

FabTex Solutions
Technical Department
2556 Piney Rd • Morganton, NC • 28566
Telephone • 828 584 1240 Fax • 828 584 0880