



Poultry and Livestock Fabrics

FABTEX 180

Product Data Sheet

PROPERTY	TEST METHOD	Typical
Weight	ASTM D5261	18 oz
Material		PVC
Thickness		23 mils
Color	Visual	White
Grab Tensile	ASTM D751-19	365 x 365 lbs
Mullen Burst	ASTM D3786	400+ PSI
Cold Crack		-40 F

This curtain is one of the heaviest and most durable curtains in the market. This product is a poly-vinyl coated curtain offers great flexibility and abrasion resistance.

Seller makes no warranty, express or implied, concerning the product furnished hereunder other than at the time of delivery it shall be of the quality and specifications stated herein. ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS EXPRESSLY EXCLUDED AND, TO THE EXTENT THAT IT IS CONTRARY TO THE FOREGOING SENTENCE ANY IMPLIED WARRANTY OF MERCHANTABILITY IS EXPRESSLY EXCLUDED. Any recommendations made by the Seller concerning uses or applications of said product are believed reliable and Seller makes no warranty of results to be obtained. This data sheet supersedes all previous data sheets for this style and is subject to change without notice. The effective date for this product data is 6/7/21.

Fabtex Solutions
Technical Department
2556 Piney Road • Morganton, NC • 28655
Telephone • 828 584 1240 Fax • 828 584 0880