



Issue Date: Sep 17, 07

STYLE F9633

TYPICAL FABRIC PROPERTIES

Property	Test Method	Units	Typical Value
Construction	ASTM D3775	threads/inch	26 x 18
Yarn Size & Type	ASTM D1907	mils	warp 20 mil monofil PP fill 20 mil monofil PP
Weave	visual	n/a	Honeycomb
Weight	ASTM D5261	oz/sq. yd.	10.2
Grab Tensile	ASTM D4632	lb	warp 475 fill 300
Burst	ASTM D3786	PSI	550
Air Permeability	ASTM D737	CFM	n/a

The above values are typical and should not be used as minimum or maximum values. Seller makes no warranty, express or implied, concerning the product furnished hereunder other than at the time of delivery it shall be of the quality and specifications stated herein. ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS EXPRESSLY EXCLUDED AND, TO THE EXTENT THAT IT IS CONTRARY TO THE FOREGOING SENTENCE ANY IMPLIED WARRANTY OF MERCHANTABILITY IS EXPRESSLY EXCLUDED. Any recommendations made by the Seller concerning uses or applications of said product are believed reliable and Seller makes no warranty of results to be obtained. This data sheet supersedes all previous data sheets for this style and is subject to change without notice.

Fabtex Solutions
Technical Department
4969 Camellia Drive • Morganton, NC • 28655
Telephone • 828 584 1240 Fax • 828 584 0880