



**Product Data Sheet**

**DDDGA36-A**  
**Silt Fence Fabric**  
 TYPICAL FABRIC PROPERTIES

**DDDGA36-A** is a woven geotextile comprised of high tenacity polypropylene slit tape yarns and monofilament yarns with blue marker yarns.

Technical Properties (Fabric)	Test Method	Unit		
			MD	CD
Mass/Unit Area	ASTM D 5261	Oz/sy	3.11	
Grab Tensile Strength	ASTM D 4632	lbs	208	115
Grab Tensile Elongation	ASTM D 4632	%	24	23
Mullen Burst Strength	ASTM D 3786	psi	297	
Puncture	ASTM D 4833	lbs	68	
Trapezoidal	ASTM D 4533	Lbs	84	63
Flow Rate	ASTM D 4491	gal/min/ft <sup>2</sup>	108	
Apparent Opening Size	ASTM D 4751	mm/SIEVE	.6/30	
Permittivity	ASTM D 4491	S-1	1.44	
Permeability	ASTM D 4491	Cm/s	.08	

The above values are typical and should not be used as minimum or maximum values. Seller makes no warranty, express or implied, concerning the product furnished hereunder other than at the time of delivery it shall be of the quality and specifications stated herein. ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS EXPRESSLY EXCLUDED AND, TO THE EXTENT THAT IT IS CONTRARY TO THE FOREGOING SENTENCE ANY IMPLIED WARRANTY OF MERCHANTABILITY IS EXPRESSLY EXCLUDED. Any recommendations made by the Seller concerning uses or applications of said product are believed reliable and Seller makes no warranty of results to be obtained. This data sheet supersedes all previous data sheets for this style and is subject to change without notice. The effective date for this product data is 7/1/14.

**FabTex Solutions**  
**Technical Department**  
 2556 Piney Rd • Morganton, NC • 28566  
 Telephone • 828 584 1240 Fax • 828 584 0880